



# Product Summary

© 2008 The Bodine Company

**bodine**

	Model Number	Lumen Output	Lamps Operated			Wattage Range	Types of Lamps Operated	Ballast Dimensions (L x W x H)	Mounting Center	Full Warranty (Years)
			1	2	3					
Linear	<b>B33</b>	3200-3400		•	•	32 - 55 W	32 W (4') T8s or (4-pin) long compacts	16.3" X 5.5" X 1.7" (414 mm X 138 mm X 44 mm)	15.7" (400 mm)	5
	<b>B30ST</b>	1450-3500	•	•		17 - 215 W 17 - 40 W	(2'-8') T8s, T9s, T10s or T12s; (4-pin) twins, quads, triple twin-tubes or long compacts	16.3" X 5.5" X 1.7" (414 mm X 138 mm X 44 mm)	15.7" (400 mm)	5
	<b>B30RCT</b>	1450-3500	•	•		17 - 215 W 17 - 40 W	(2'-8') T8s, T9s, T10s or T12s; (4-pin) twins, quads, triple twin-tubes or long compacts	16.3" X 5.5" X 1.7" (414 mm X 138 mm X 44 mm)	15.7" (400 mm)	5
	<b>B30</b>	1450-3500	•	•		17 - 215 W 17 - 40 W	(2'-8') T8s, T9s, T10s or T12s; (4-pin) twins, quads, triple twin-tubes or long compacts	16.3" X 5.5" X 1.7" (414 mm X 138 mm X 44 mm)	15.7" (400 mm)	5
	<b>B35ST</b>	1800-3000	•			20 - 55 W	(2'-4') T5, T8, T9, T10 or T12	16.3" X 5.5" X 1.7" (414 mm X 138 mm X 44 mm)	15.7" (400 mm)	5
	<b>B50ST</b>	1100-1400	•	•		17 - 215 W 17 - 40 W	(2'-8') T8s, T9s, T10s or T12s; (4-pin) long compacts	13.3" X 2.4" X 1.5" (339 mm X 60 mm X 38 mm)	12.8" (325 mm)	5
	<b>B50RCT</b>	1100-1400	•	•		17 - 215 W 17 - 40 W	(2'-8') T8s, T9s, T10s or T12s; (4-pin) long compacts	13.3" X 2.4" X 1.5" (339 mm X 60 mm X 38 mm)	12.8" (325 mm)	5
	<b>B50</b>	1100-1400	•	•		17 - 215 W 17 - 40 W	(2'-8') T8s, T9s, T10s or T12s; (4-pin) long compacts	13.3" X 2.4" X 1.5" (339 mm X 60 mm X 38 mm)	12.8" (325 mm)	5
	<b>B60</b>	600-700	•	•		17 - 215 W 17 - 40 W	(2'-8') T8s, T10s or T12s; (4-pin) long compacts	9.4" X 2.4" X 1.5" (238 mm X 60 mm X 38 mm)	8.9" (226 mm)	3
	<b>B70A</b>	600-700	•			17 - 215 W	(2'-8') T8, T10 or T12; (4-pin) long compact	9.4" X 2.4" X 1.5" (238 mm X 60 mm X 38 mm)	8.9" (226 mm)	3
	<b>B90</b>	500-600	•			17 - 40 W	(2'-4') T8, T9, T10 or T12; (4-pin) long compact	9.4" X 2.4" X 1.5" (238 mm X 60 mm X 38 mm)	8.9" (226 mm)	1
<b>B100</b>	350-450	•			17 - 40 W	(2'-4') T8, T9, T10 or T12; (4-pin) long compact	9.4" X 2.4" X 1.5" (238 mm X 60 mm X 38 mm)	8.9" (226 mm)	1	
Compact	<b>B74CST</b>	350 - 1000	•	•		13 - 55 W	(4-pin) twins, quads or triple twin-tubes; T5 circline; (4-pin) long compacts	13.3" X 2.4" X 1.5" (339 mm X 60 mm X 38 mm)	12.8" (325 mm)	5
	<b>B75C</b>	600-1200	•			32 - 70 W	(4-pin) triple twin-tube	13.3" X 2.4" X 1.5" (339 mm X 60 mm X 38 mm)	12.8" (325 mm)	5
	<b>B84CG</b>	700-1250	•			13 - 42 W	(4-pin) twin, quad or triple twin-tube; T5 circline; (4-pin) long compact	12" X 2.4" X 1.5" (305 mm X 60 mm X 38 mm)	11.5" (292 mm)	2
	<b>B4CFG</b>	700-1250	•			13 - 42 W	(4-pin) twin, quad or triple twin-tube; T5 circline; (4-pin) long compact	9.4" X 2.6" X 1.5" (238 mm X 67 mm X 38 mm)	8.9" (226 mm)	5
	<b>B94CG</b>	300-750	•			13 - 42 W	(4-pin) twin, quad or triple twin-tube	9.4" X 2.4" X 1.5" (238 mm X 60 mm X 38 mm)	8.9" (226 mm)	2
	<b>BDL94C*</b>	300-750	•	•		13 - 42 W 13 - 38 W	(4-pin) twins, quads or triple twin-tubes	9.4" X 2.4" X 1.5" (238 mm X 60 mm X 38 mm)	8.9" (226 mm)	2
	<b>B413</b>	200-625	•			5 - 13 W	(2-pin) twin or quad	9.4" X 2.4" X 1.5" (238 mm X 60 mm X 38 mm)	8.9" (226 mm)	2
	<b>B463</b>	300-650	•			10 - 26 W	(2-pin) quad or triple twin-tube	9.4" X 2.4" X 1.5" (238 mm X 60 mm X 38 mm)	8.9" (226 mm)	2
	<b>B426</b>	450-950	•	•		10 - 26 W	(2-pin) twins, quads or triple twin-tubes	12.0" X 2.4" X 1.5" (305 mm X 60 mm X 38 mm)	11.5" (292 mm)	2
Low-Profile	<b>LP400</b>	450	•			32 W	32 W (4') T8	14.1" X 1.5" X 1.0" (356 mm X 38 mm X 25 mm)	13.7" (348 mm)	3
	<b>LP500</b>	400-520	•			14 - 28 W	Standard T5	18.5" X 1.18" X 1.0" (470 mm X 30 mm X 25 mm)	18.1" (460 mm)	5
	<b>LP550</b>	390-700	•			14 - 55 W	Standard or HO T5 or T8	18.5" X 1.18" X 1.18" (470 mm X 30 mm X 30 mm)	18.1" (460 mm)	5
	<b>LP600</b>	600-1325	•			14 - 55 W	Standard or HO T5 or T8	21.5" X 1.18" X 1.18" (546 mm X 30 mm X 30 mm)	21.1" (536 mm)	5
	<b>LP600-STU</b>	600-1325	•			14 - 55 W	Standard or HO T5 or T8; (4-pin) long compacts	22.5" X 1.18" X 1.18" (572 mm X 30 mm X 30 mm)	22.1" (561 mm)	5
	<b>B50LP</b>	750-1250	•	•		17 - 215 W 17 - 40 W	(2'-8') T8s, T10s or T12s; (4-pin) long compacts	21.5" X 1.18" X 1.18" (546 mm X 30 mm X 30 mm)	21.1" (536 mm)	5

\*The BDL94C may not properly operate low mercury compact lamps.



# Product Summary

© 2008 The Bodine Company

**bodine**

	Model Number	Lumen Output	Lamps Operated		Wattage Range	Types of Lamps Operated	Ballast Dimensions (L x W x H)	Mounting Center	Full Warranty (Years)
			1	2					
Cold-Pak®	B50Cold-Pak	800-1200	•	•	17 - 215 W 17 - 40 W	(2'-8") T8s, T9s, T10s or 12s; (4-pin) long compacts	13.3" X 2.4" X 1.5" (339 mm X 60 mm X 38 mm)	12.8" (325 mm)	5
	B4CF1	700-1250	•		13 - 42 W	(4-pin) twin, quad or triple twin-tube; T5 circline; long compact	9.4" X 2.6" X 1.5" (238 mm X 67 mm X 38 mm)	8.9" (226 mm)	5
	B4CF2	700-1250	•		13 - 42 W	(4-pin) twin, quad or triple twin-tube; T5 circline; long compact	9.9" X 2.6" X 1.5" (251 mm X 67 mm X 38 mm)	9.4" (239 mm)	5

	Model	Function	VAC Options	Dimensions	Full Warranty (Years)
ARC Keeper®	AK400PLS	Maintains the arc with one 200 - 400 W metal halide pulse-start lamp	120/277; 120/208; 120/240	12.25" X 7.25" X 1.75" (311 mm X 184 mm X 44 mm)	5
	AK175PLS	Maintains the arc with one 100 - 175 W metal halide pulse-start lamp	120/277; 120/208; 120/240	12.25" X 7.25" X 1.75" (311 mm X 184 mm X 44 mm)	5
	AK400PRB	Maintains the arc with one 400 or 360 W metal halide probe-start lamp	120/277	12.25" X 7.25" X 1.75" (311 mm X 184 mm X 44 mm)	5
	AK400PRB-SP	For use with installations not providing an unswitched line	120/277	12.25" X 7.25" X 1.75" (311 mm X 184 mm X 44 mm)	5
	AK250PRB	Maintains the arc with one 250 or 225 W metal halide probe-start lamp	120/277	12.25" X 7.25" X 1.75" (311 mm X 184 mm X 44 mm)	5
	AK175PRB	Maintains the arc with one 175 or 150 W metal halide probe-start lamp	120/277	12.25" X 7.25" X 1.75" (311 mm X 184 mm X 44 mm)	5

	Model	Lumen Output	Lamps Operated			Types of Lamps Operated	Illumination Time	Ballast Dimensions (L x W x H)	Mounting Center	Full Warranty (Years)
			1	2	3					
GEN Series™	GEN3	4700-7900		•	•	32 W (4') T8s; 40-55 W (4-pin) long compacts	Up to 4 minutes	13.3" x 2.4" x 1.5" (339 mm x 60 mm x 38 mm)	12.8" (325 mm)	5
	GEN1	1050-3200	•			17-32 W (2'-4') T8; 20-40 W (2'-4') T10 or T12; 18-55 W (4-pin) long compact	Up to 5 minutes	9.4" x 2.4" x 1.5" (238 mm x 60 mm x 38 mm)	8.9" (226 mm)	5

	Model	Description	Load Rating	Dimensions	Full Warranty (Years)
GTD™ Family	GTD Generator Transfer Device	Transfer device; compatible with fluorescent only	3 amps max	8" X 1.18" X 1.18" (204 mm X 30 mm X 30 mm)	5
	GTD20A Emergency Lighting Relay Control Device	Transfer or bypass device; compatible with fluorescent, incandescent and HID	20 amps max	9" X 6" X 3.5" (229 mm X 152 mm X 89 mm)	5

	Model	Function	Dimensions	Accessories	Full Warranty (Years)
CheckMate™	CheckMate ET1	Provides remote control testing feature to existing exit signs and emergency lighting wall packs	4.06" X 1.26" X 1.03" (102.9 mm X 31.8 mm X 26.2 mm)	One handheld WHRCT remote control transmitter (sold separately)	5

	Model	Function	Lumen Output	Lamps Operated		Wattage Range	Types of Lamps Operated	Full Warranty (Years)
				1	2			
Central Battery	CB90 - 48	Provides backup lighting to fluorescent fixtures that have dedicated systems and a 48VDC central battery supply	1000-3100	•	•	17-215 W 17-40 W	(2'- 8') T8s, T9's, T10s or T12s; (4-pin) compacts	1